136 Series Hydraulic ToolsDieless 4 Indent Crimp Tool



DMC's dieless four-indent crimpers provide a symmetrical four-sided crimp (at 90° intervals) intended to crimp copper and aluminum terminals and splices 8 AWG - 750 MCM. All of these tools have 6 tons of crimp force. The crimp pressure against the resistance of the metal conductor assembly will cause the tool to crimp to a depth where there is metal to metal bottoming (gas tight crimp joint on aluminum and soft copper).

These tools feature standard triangular indenters. Various other indenter shapes are available. Consult DMC.



HC136

HC136 FEATURES

- L x W x H: 21 x 2.3 x 5.4 (in) 610 x 137 x 58 (mm)
- Weight 13 pounds (5.9 kg)
- Automatic relief valve to prevent over-compression
- Release lever for opening indenters
- 360° rotating head
- · Rapid advance close by rotating handle

The **XHC136** is a hand held remote crimp head. An open frame version of this tool is available (Part # **XHC136C**). Both of these tools require a pump, several pump options are listed below.



XHC136

XHC136 FEATURES

- L x W x H: 13.3 x 2.5 x 5.4 (in) 337 x 65 x 137 (mm)
- Weight: 8.5 lb (38.6 kg)



XHC136C

XHC136C FEATURES

- L x W x H: 13.3 x 2.5 x 5.4 (in) 337 x 65 x 137 (mm)
- Weight: 8.5 lb (38.6 kg)
- Open frame



Battery Equivalent

DMC offers several 10 KSI pumps to power the XHC136 and XHC136C remote crimp heads. Two powered pumps: the **HPU13M** battery powered pump, and the **HPU11M** pneumatic powered pump. Two portable manual options: the **HPU12M** hand pump and the **HPU15M** foot pump. All pumps include a heavy duty, ten-foot long hose and heavy duty couplings equipped with screw-on MS fittings and dust covers to complete the connection between pump and crimper (Part # **12-4040**).









PU12M HPU15M