136 SERIES
DIELESS 4-INDENT CRIMP TOOLS

The 136 series is a collection of dieless crimp tools that are suitable for crimping copper and aluminum contacts, terminals, and splices sizes 8 AWG to 750 MCM. All 136 series tools produce 6 tons of crimp force and are equipped with 360° rotating heads that enhance maneuverability.

Battery Hydraulic

HCE136C

Average cycle time of 2 seconds

150 crimps per charge

Crimp data is viewable on the LED display or on an app via Bluetooth®

Includes an automatic indenter retraction system to prevent over compression

Includes a carrying case, two 18v, 3.0 AMP batteries, and one battery charger.
15.5" L x 2" W x 13.5" H and 11.6 lbs

Manual Hydraulic

HC136

Two stage pump facilitates faster crimping

Equipped with an automatic relief valve to prevent over-compression

Packaged in a carrying case for convenient storage and enhanced portability.

Sold in a carrying case.
21" L x 2.3" W x 5.4" H and 13 lbs

Remote Hydraulic

XHC136

XHC136C

Purpose-built for bench-mounted applications

Seamlessly operates with various DMC pumps to ensure flexibility in your work environment

C-style XHC136C provides enhanced convenience for effortless insertion and removal of wires

13.3" L x 2.5" W x 5.4" H and 8.5 lbs

©Daniels Manufacturing Corporation

136 SERIES
DIELESS 4-INDENT CRIMP TOOLS

DMC offers a variety of hydraulic powered pumps to power our remote crimp head tools. Each of these tools provide a maximum output of 10,000 psi. All pumps include a heavy duty, ten-foot long hose and heavy duty couplings equipped with screw-on MS fittings and dust covers to complete the connection between pump and crimper (Part # 12-4040, M5259/2-01). The HPU series pumps meet the requirements of the SAE AS5259/2 spec for large gauge crimp tools, dies and terminals.

HPU11M

Pneumatic Hydraulic

Foot operated pump with pressure pedal, release pedal, lock, and hydraulic gauge

Twice as fast as traditional air driven hydraulic pumps

Variable speed and pressure control

13.8" L x 11.5" W x 6.3" H and 19.4 lbs.
Requires input air of 30-125 psi.

HPU12M
M5259/2-02

Manual Hydraulic

Two speed hand-actuated pump

Ideal for field use or shops where pneumatic air or electricity is not available

Internal pressure relief valve for overload protection

22" L x 4.8" W x 7.3" H and 8.6 lbs.

HPU13M

Battery

FEATURES

Ideal for the field or shop use where pneumatic air or electricity is not available

LCD display indicates battery charge and health

One-step pump automatically retracts dies in tool when connected

14" L x 6.5" W x 11.3" H and 14.2 lbs.
Includes two Lithium-ion 18V battery and a charger

HPU15M
M5259/2-03

Manual Hydraulic

FEATURES

Two speed foot-actuated pump

Ideal for field use or shops where pneumatic air or electricity is not available

Internal pressure relief valve for overload protection

23.8" L x 7.8" W x 7.5" H and 16 lbs.

Refurbishment Services:
To ensure the longevity of your investment, DMC offers kit refurbishment and calibration services.

NOTICE:
DMC reserves the right to change the kit contents, coverage, and construction.