

Battery Powered Safe-T-Cable™ Tool .062" Cable Size



This battery-powered Safe-T-Cable tool provides adjustable tension to crimp .062" cable faster and easier. New features allow the operator to track tool performance, users, and projects. Crimp data is viewable in real-time on the LED display, or can be downloaded via Bluetooth® to an app.

This tool features a rotary tension mechanism that can be adjusted to precise cable tension requirements. As with all Safe-T-Cable tools, the noses are interchangeable and come in various lengths including 3", 5", 7", and 9".



CAPABILITIES

- .062" Diameter Safe-T-Cable
- Max. Crimp Force: 4 Tons (35.6 kN)
- Avg. Crimp Time: 4 seconds
- Avg. Crimps per Charge: 100 (Approx 200 with Extended Life Battery)

SPECIFICATIONS

- Weight (with battery): 2.8 lb (1.3 kg)
- Sound Level: 75 db (A) at 1 meter
- Vibration: < 8.2 ft/s² (2.5 m/s²)
- Hydraulic Oil: Shell Tellus® T-15

INCLUDED

- Carrying case
- Two 18V, 2.0 Ah, Lithium Ion batteries
- One battery charger

FEATURES

- Bluetooth connectivity
- Tracks number and quality of crimps
- Ergonomic design allows one-handed operation
- Head rotates 350°
- LED light illuminates work area

BATTERY (Part # HDE-LI-B)

- 18 VDC, 2.0 Ah, Lithium Ion
- Charging Time: 22 minutes

OPTIONAL EXTENDED LIFE BATTERY (Part # HDE-LI3-B)

- 18 VDC, 3.0 Ah, Lithium Ion
- Charging Time: 45 minutes

BATTERY CHARGER

- 120 VAC Part # HDE-LI-120C
- 230 VAC Part # HDE-LI-230C

VAC POWER ADAPTERS

- 120 VAC Part # HDE-120AC-A
- 230 VAC Part # HDE-230AC-A



BATTERY AND MANUAL TOOL PART NUMBERS

CABLE DIAMETER	NOSE LENGTH	MANUAL TOOL PART #	BATTERY TOOL PART #
.062"	5"	SCTH625	SCTE625C
.062"	7"	SCTH627	SCTE627C
.062"	9"	SCTH629	SCTE629C

Other nose sizes are available. Contact DMC for part numbers.