



|           |                |
|-----------|----------------|
| HOLE DIA. | REMARKS        |
| Ø .258    | ↓ .752<br>MIN. |

| REVISIONS |         |                   |              |
|-----------|---------|-------------------|--------------|
| REV. SYM. | ECO NO. | DESCRIPTION       | BY DATE      |
| A         |         | ORIGINAL RELEASE  | DVC 2/1/85   |
| B         |         | ADDED "MIN." DEL. | Ch... 2/6/85 |

|                  |               |                     |                 |
|------------------|---------------|---------------------|-----------------|
| DEUTSCH SERIE DS | TYPE CONTACTS | 8.98mm <sup>2</sup> | WIRE SIZE       |
| 047.1325.08      | P             | 2                   | SELECTOR NUMBER |
| 047.1326.08      | S             |                     |                 |

USE WITH M300BT

|   |             |   |                          |  |  |
|---|-------------|---|--------------------------|--|--|
| MATERIAL/HEAT TREAT                         |             | FINISH  |                          | RESTRICTED & CONFIDENTIAL  |  |
| ITEM  | PART NUMBER | REC'D   | DESCRIPTION/NOMENCLATURE | CONFIDENTIAL INFORMATION, PROPERTY OF DANIELS MFG. CORP. NOT TO BE DISCLOSED TO OTHERS. REPRODUCED OR USED FOR ANY OTHER PURPOSE, EXCEPT AS AUTHORIZED IN WRITING BY DANIELS MFG. CORP. MUST BE RETURNED TO DANIELS MFG. CORP. ON COMPLETION OF ORDER OR OTHER PURPOSE FOR WHICH LENT. |  |
| DRN   | DATE        | CHK'D   | DATE                     | TOLERANCE: UNLESS OTHERWISE SPECIFIED FRACTIONS 1/32 APPROX 1/2 DECIMALS<br>.X ± .000 .XX ± .010 .XXX ± .005 .XXXX ± .0005 REMOVE BURRS & BREAK SHARP EDGES .005-.015  |  |
| APP'D                                       | DATE        | APP'D   | DATE                     | WHERE USED: SIZE SCALE SUPERSEDES DATE<br>A NTS PART NO. SP604-ENV REV. B  |  |
| ENVELOPE DRAWING<br>SINGLE POSITION DRAWING |             | DANIELS MANUFACTURING CORP.<br>ORLANDO, FLORIDA<br>CAGE 11851 |                          |  |  |